



Firma: STD Comp  
 Adresa: Vojvode Putnika 51  
 Telefon: 069/853-90-69  
 Fax:  
 PIB: 111971285  
 E-mail: stdcomp015@gmail.com

## Switch TP Link TL-SG108PE 8-port Gigabit POE

Šifra: 9003  
 Kategorija proizvoda: SWITCH UREĐAJI  
 Proizvođač: NEDEFINISAN

Cena: **8.360,00** rsd.



<b>HARDWARE FEATURES</b>	
<b>Standards and Protocols</b>	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p
<b>Interface</b>	8 10/100/1000Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
<b>Network Media</b>	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
<b>Fan Quantity</b>	Fanless
<b>Power Supply</b>	External Power Adapter 100VAC ~ 240VAC (Output: 48VDC / 1.25A)
<b>PoE+ Ports(RJ45)</b>	
<b>PoE Ports (RJ45)</b>	Standard: 802.3 af compliant PoE Ports: Port 1- Port 4 PoE Power Budget: 55W
<b>Dimensions ( W x D x H )</b>	6.2 × 4.0 × 1.0 in (158 × 101 × 25 mm)
<b>Max Power Consumption</b>	5.2W with no PoE device connected 65.2W with 55W PoE devices connected
<b>Max Heat Dissipation</b>	17.6 BTU/h (with no PD connected) 222.4 BTU/h (with 55W PD connected)
<b>PERFORMANCE</b>	
<b>Switching Capacity</b>	16Gbps
<b>Packet Forwarding Rate</b>	11.9Mpps
<b>MAC Address Table</b>	4K
<b>Packet Buffer Memory</b>	1.5Mb
<b>Jumbo Frame</b>	15KB
<b>SOFTWARE FEATURES</b>	
<b>Quality of Service</b>	Support Port-Based/802.1p/DSCP priority Support 4 priority queues Rate Limit Storm Control
<b>L2 Features</b>	IGMP Snooping V1/V2/V3 Link Aggregation Port Mirroring Cable Diagnostics Loop Prevention

<b>SOFTWARE FEATURES</b>	
<b>VLAN</b>	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN
<b>Management</b>	Web-based GUI Easy Smart Configuration Utility
<b>Transmission Method</b>	Store-And-Forward
<b>OTHERS</b>	
<b>Certification</b>	FCC, RoHS
<b>Package Contents</b>	TL-SG108PE Power Adapter Installation Guide Rubber Feet
<b>Environment</b>	Operating Temperature: 0?~40? (32?~104?) Storage Temperature: -40?~70? (-40?~158?) Operating Humidity: 10%~90%RH non-condensing Storage Humidity: 5%~95%RH non-condensing