



Firma: STD Comp
Adresa: Vojvode Putnika 51
Telefon: 069/853-90-69
Fax:
PIB: 111971285
E-mail: stdcomp015@gmail.com

Tenda N301 Wireless N300 Ruter, WISP/univ.
repeater/WDS-bridge/client+AP/WPS, 3L/1W
2x5dB

Šifra: 9735
Kategorija proizvoda: RUTERI I EKSTENDERI
Proizvođač: TENDA

Cena: **1.910,00** rsd.



N301 je zameski proizvod za : N150 (150N Tenda ruter) , N3 (150N Tenda ruter) Hardware Features
Protocols & Standards IEEE 802.3/3U IEEE 802.11n/g/b Interface 1 10/100Mbps WAN Port 3 10/100Mbps
LAN Ports Antenna 2 fixed 5dbi Omni Directional antennas Button 1 Reset/WPS Button Dimensions (L*W*H)
mm 127.4mm*90.5mm*26mm Wireless Features Wireless Link Rate IEEE 802.11n: up to 300Mbps IEEE
802.11g: up to 54Mbps IEEE 802.11b: up to 11Mbps Frequency Range (GHz) 2.412GHz-2.472GHz Working
Mode Universal Repeater AP WISP WDS Bridge Wireless Security 64/128bit WEP WPA-PSK WPA2-PSK WPS
support Wireless Function Enable/Disable Wireless Radio Wireless Access Control Reception Sensitivity b
mode:1M -92dBm@8% 11M -87dBm@8% PER; g mode:54M -72dBm@8% PER; n mode:72.2M -68dBm@8%
PER; 150M -68dBm@8% PER; Software Features Internet Connection Type Dynamic IP?PPPOE?Static
IP?L2TP?PPTP DHCP Server Built-in DHCP server DHCP Client List Address Reservation Virtual Server Port
Forwarding DMZ Host Parental Control Client Filter Mac Filter Websites Filter Dynamic DNS No-IP dyndns
VPN Pass-Through PPTP L2TP Other Advanced Function Bandwidth Control Mac Address Clone Remote Web
Management System Log Others Package Contents Wireless N300 Easy Setup Router N301 Quick
Installation Guide Ethernet cable Power adapter Resources CD Environment Operating Temperature:
0?~40? Storage Temperature: -40?~70? Operating Humidity: 10%~90% non-condensing Storage Humidity:
5%~90% non-condensing Certificates FCC, CE,RoHs Nacin podesavanja UNIVERSAL REPEATER:
<http://www.tendacn.com/en/faq/2913.html> Tenda Mrežni wireless adapteri i ruteri adsl 3g tp-link ## mct